

SPECIFICATIONS

	SprayStream 10i	SprayStream 15i Trolley	SprayStream 25i Trolley	SprayStream 25i CART single	SprayStream 25i PLATFORM	SprayStream 25i Self Supporting	SprayStream 35i	SprayStream 35i HP	SprayStream 35i Self supporting	SprayStream 50i Self supporting	SprayStream 50i-60i-70i	SprayStream 50i-60i-70i HP High efficiency	SprayStream 50i POWER	SprayStream 50i TOWER (4m)	SprayStream 50i Vertical Tank	SprayStream 80i	SprayStream 100i
Dimensions																	
LxWxH (mm)	500-360-630	1350-600-900	1350-1100-1550	1350-1200-1950	1250-1100-2700	5500-1700-3100	1450-1600-2000	1450-1600-2000	2900-1400-3200	5300-2450-3100	1550-1600-2350	1550-1600-2350	4700-1820-3250	1550-1600-6500	1550-1600-4500	1800-1600-2350	1800-1600-2350
Weight (kg)	15kg (excl. bat)	60	210	200 - 175	285	1100-1350	350	350	700	2200	470 - 500 - 530	470 - 500 - 530	2000	900	900	570	600
Throw (m)	10	15	25	25	30	30	35	35	35	50	50-70	50-70	50	60	55	80	100
Specifications																	
Pump (kW)	-	0.75	1.5	2,2 - 1,5	2,2 - 1,5	1.1	1,5 - 3	2.2	1.5	4	4	5.5	5.5	5.5	5.5	5.5	5.5
Turn device	-	-	-	•	MAN	MAN	•	•	•	•	•	•	•	•	•	•	•
Total load (A)	-	7	6-9	9	9	6-8	16	10	16	25	25 - 28 - 39	25 - 28 - 39	28	25	25	49	56
Plug 5pin	1x230VAC	1x230VAC	16	16	16	16	16	16	16	33	32 - 32 - 63	32 - 63 - 63	32	32	32	63	63
Min. advised genset (KVA)		3	8	10	10	-	12	10	10	-	18 - 25 - 35	18 - 25 - 35	-	18	18	45	60
Specifications H ² O																	
Pressure at machine (min-max)	1.5	2-5	2-5	2-5	2-5	-	2-5	2-5	-	-	2-8	2-5	2-8	2-8	2-5	2-8	2-8
Filter	•	•	•	•	•	-	•	•	-	-	•	•	•	•	•	•	•
Nozzles	5	4	15	15	15	15	20	30	20	30	30	60	30	30	30	30	30
Waterpressure (Bar)	1.5	100	80	20-80	20-80	20	20	80	20	20	20	80	20	20	20	20	20
Waterflow (l/h)*	40-60	10-60	400	900 - 400	900 - 400	100-1000	1200	800	1200	1300 - 2700	2700	1400	1800-3600	3600	2700	4500	5400
Connection	1/2" BSP m.	1/2" BSP m.	1/2" BSP m.	1" BSP m.	1/2" BSP m.	-	1" BSP m.	1" BSP m.	-	2" BSP	1" BSP m.	1" BSP m.	1" BSP m.	1" BSP m.	1" BSP m.	1" BSP m.	6/4" BSP m.
Other																	
Telescopic tower 5,5m	-	-	-	-	•	-	-	-	-	-	-	-	-	-	-	-	-
GENSET (KVA)	-	-	-	-	-	•	-	-	Upon demand	24(D)	-	-	18(D)	-	-	-	-
Watertank (l)	-	-	-	-	-	2500	-	-	1250	2000	-	-	-	-	3000	-	-
Options																	
Detection Pressure	NA	•	•	o	•	•	o	o	•	•	o	o	•	•	•	o	o
Membrane valve	NA	•	•	o	•	-	o	o	-	-	o	o	•	•	-	o	o
Remote control	NA	NA	o	o	o	o	o	o	o	•	o	o	•	o	o	o	o
Lifting bracket	NA	NA	NA	o	NA	NA	o	o	NA	NA	o	o	NA	NA	NA	o	o
Electric vertical pitch	NA	NA	NA	NA	NA	NA	o	o	o	o	o	o	•	•	•	o	o
Splitable nozzling (man)	NA	NA	NA	NA	NA	NA	o	o	o	o	o	NA	•	NA	NA	o	o
Splitable nozzling (elec)	NA	NA	NA	NA	NA	NA	NA	NA	NA	o	o	NA	o	o	o	o	o
Double nozzling	NA	NA	o	o	o	o	NA	NA	NA	o	o	•	o	o	o	o	o
Fixed angle detector	NA	NA	NA	NA	NA	NA	NA	o	NA	•	o	o	•	•	•	o	o
High pressure pump	NA	•	•	•	NA	NA	NA	•	NA	NA	NA	•	NA	NA	NA	NA	NA
Stainless steel cabinet	NA	NA	o	o	o	o	o	o	o	o	o	o	o	o	o	o	o
3 wheels	NA	NA	NA	o	NA	NA	o	o	NA	NA	o	o	NA	NA	NA	o	o
High output pump	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	o	NA	•	•	•	•	•
Rotation Device	NA	NA	NA	•	o	o	•	•	•	•	•	•	•	•	•	•	•
Feeding pump	NA	NA	NA	NA	NA	NA	o	o	NA	NA	o	o	o	NA	o	NA	NA
Heating package -15°C	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	o	NA	NA	o	o	o	o
Phase controller	•	NA	o	o	o	o	NA	o	NA	o	o	o	•	o	o	o	o
VFD pump	NA	NA	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request	UPON Request

Specifications are subject to change without notice

•	standard
o	option
-	not available

(*) Waterflow can be adjusted according to the application
 (**) adjustable